



NOTES:

- 1. ELECTRICAL: 16,000 WATTS(+/-10%), 208 VOLTS 3-PHASE WITH DOWNSTREAM RTD/PT100 INDEPENDENT MEDIUM SENSOR ALL WETTED PARTS WILL BE 316 STAINLESS STEEL
- 2. PART TESTED TO 80 PSI AT 20-25C
- 3. ASSEMBLY CLEANED TO BCE SPEC UT-19

<p>The information given herein is based on data believed to be accurate, but BCE makes no expressed or implied warranties as to its accuracy and assumes no liability arising out of its use by others. This information does not constitute a license to use or infringe on any patents</p>	<p>UNLESS OTHERWISE SPECIFIED:</p>		<p>PART. NO.</p>	
	<p>DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .005 THREE PLACE DECIMAL ± .001</p>		<p>BCE</p>	
<p>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELLOVE CO. ENGINEERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELLOVE CO. ENGINEERS IS PROHIBITED.</p>	<p>INTERPRET GEOMETRIC TOLERANCING PER:</p>		<p>TITLE:</p>	
	<p>MATERIAL SEE DWG</p>		<p>Mini Clean Flow Heater - Large DI Water</p>	
	<p>FINISH N/A</p>		<p>SIZE A</p>	<p>DWG. NO. BCE11240</p>
<p>DO NOT SCALE DRAWING</p>		<p>SCALE: NTS</p>	<p>WEIGHT: N/A</p>	<p>SHEET 1 OF 1</p>